

Wall mounted unit

FTXA-AS + RXA-A / RXA-B



stylish



Coanda effect - cooling



Coanda effect - heating



Intelligent thermal sensor



Online controller



Multi model application

Where innovation meets creativity

- › Compact design in silver
- › Perfect temperature distribution thanks to Coanda effect
- › Intelligent thermal sensor: air flow is adjusted when detecting temperature differences
- › Daikin Flash Streamer technology: powerful air purification
- › Practically inaudible
- › Online controller via app
- › Bluevolution range: lower environmental impact
- › Seasonal efficiency values up to A+++ in cooling and heating

FTXA-AS + RXA-A / RXA-B



Efficiency data		FTXA + RXA	20AS + 20A	25AS + 25A	35AS + 35A	42AS + 42B	50AS + 50B
Cooling capacity	Min./Nom./Max.	kW	1.3/2.0/2.6	1.3/2.5/3.2	1.4/3.4/4.0	1.7/4.2/5.0	1.7/5.0/5.3
Heating capacity	Min./Nom./Max.	kW	1.30/2.50/3.50	1.30/2.80/4.70	1.40/4.00/5.20	1.70/5.40/6.00	1.70/5.80/6.50
Power input	Cooling	Min./Nom./Max.	kW	0.27/0.43/0.63	0.27/0.56/0.78	0.31/0.78/1.04	-/1.05/-
	Heating	Min./Nom./Max.	kW	0.25/0.50/0.91	0.25/0.56/1.22	0.26/0.99/1.67	-/1.31/-
Space cooling	Energy efficiency class			A+++			A++
	Capacity	Pdesign	kW	2.00	2.50	3.40	4.20
	SEER			8.75	8.74	8.73	7.50
	Annual energy consumption		kWh/a	80	101	137	196
Space heating (Average climate)	Energy efficiency class			A+++			A++
	Capacity	Pdesign	kW	2.40	2.45	2.50	3.80
	SCOP/A			5.15			4.60
	Annual energy consumption		kWh/a	653	666	680	1,150
Nominal efficiency	EER		4.70	4.46	4.37	3.99	3.68
	COP		5.00			4.04	4.12
Energy labeling Directive		Cooling/Heating	A/A				

Indoor unit		FTXA	20AS	25AS	35AS	42AS	50AS			
Dimensions	Unit	HeightxWidthxDepth	mm							
			295x798x189							
Weight	Unit		kg							
			12							
Air filter	Type		Removable / washable							
Fan	Air flow rate	Cooling	Silent operation/Low/	m³/min		4.6/6.1/8 /11.0	4.6/6.1/9 /11.5	4.6/6.1/9 /11.9	4.6/7.2/10 /13.1	5.2/7.6/10 /13.5
		Heating	Silent operation/Low/	m³/min		4.5/6.4/8.7 /10.9	4.5/6.4/9.0 /11.1	4.5/6.4/9.0 /11.5	5.2/7.7/10.5 /14.6	5.7/8.2/11.1 /15.1
Sound power level	Cooling		dBA		57		60			
Sound pressure level	Cooling	Silent operation/Low/High	dBA		19/25/39	19/25/40	19/25/41	21/29/45	24/31/46	
	Heating	Silent operation/Low/High	dBA		19/25/39	19/25/40	19/25/41	21/29/45	24/31/46	
Control systems	Infrared remote control		ARC466A58							
	Wired remote control		BRC073							
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50/220-240					

Outdoor unit		RXA/RXA	20A	25A	35A	42B	50B
Dimensions	Unit	HeightxWidthxDepth	mm			734x870x373	
			550x765x285				
Weight	Unit		kg			50	
			32				
Sound power level	Cooling		dBA		59	61	62.0
	Heating		dBA		59	61	62.0
Sound pressure level	Cooling	Nom.	dBA		46	49	48.0
	Heating	Nom.	dBA		47	49	48.0
Operation range	Cooling	Ambient	Min.~Max.	°CDB			-10~46
	Heating	Ambient	Min.~Max.	°CWB			-15~18
Refrigerant	Type		R-32				
	GWP		675.0				
Piping connections	Charge		kg/TCO2Eq		0.76/0.52		1.10/0.75
	Liquid	OD	mm		635		64
	Gas	OD	mm		9.50		12.7
	Piping length	OU - IU	Max.		m		20
	Additional refrigerant charge		kg/m		0.02 (for piping length exceeding 10m)		
	Level difference		IU - OU	Max.		m	
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50/220-240		
Current - 50Hz	Maximum fuse amps (MFA)		A		10	13	-

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)

Responsible Editor

ECPEN19-051

09/2018

