



Air cooled screw  
chiller, standard  
efficiency, extra  
low sound

EWAD-D-SX

**R-134a**



Screw compressor

- › 2 truly independent refrigerant circuits
- › Stepless single-screw compressor
- › Optimised for use with R-134a

- › Large operation range (ambient temperature down to  $-18^{\circ}\text{C}$ )
- › MicroTech III controller with superior control logic and easy interface


# EWAD-D-SX



Cooling only				EWAD-D-SX											
				210	230	250	270	290	300	310	370	410	450	490	
Cooling capacity	Nom.	kW		202	230	252	270	285	298	308	369	412	449	490	
Power input	Cooling	kW		80.8	86.0	94.4	105	115	127	137	150	171	175	189	
Capacity control	Method	Stepless													
	Minimum capacity	%		12.5											
EER				2.50	2.68	2.67	2.56	2.47	2.35	2.25	2.46	2.41	2.56	2.60	
ESEER				3.29	3.52	3.41	3.44	3.34	3.29	3.15	3.14	3.39	3.50	3.47	
IPLV				3.82	4.08	3.99	4.01	3.92	3.84	3.69	4.03	3.90	3.98	3.90	
Dimensions	Unit	Height	mm	2,420											
		Width	mm	2,234											
		Depth	mm	3,139	4,040						4,940				
Weight	Unit	kg		3,110	3,475		3,425		3,430		3,560	4,302	4,506	4,581	
	Operation weight	kg		3,200		3,590				3,735	4,472	4,676	4,746		
Water heat exchanger	Type	Single pass shell & tube													
	Water flow rate	Cooling	Nom.	l/s	9.7	11.0	12.1	12.9	13.7	14.3	14.7	17.7	19.7	21.5	23.5
	Water pressure drop	Cooling	Nom.	kPa	45	34	38		35	38	41	45	44	50	45
	Water volume			l	90	115		165		160		175	170		165
Air heat exchanger	Type	High efficiency fin and tube type with integral subcooler													
Compressor	Type	Single screw compressor										Asymmetric single screw compressor			
	Quantity	2													
Fan	Type	Direct propeller													
	Quantity			6	8						9	10			
	Air flow rate	Cooling	Nom.	l/s	12,876	17,892	17,169				26,496	28,982	33,120		
	Speed			rpm	500										
Sound power level	Cooling	Nom.	dB(A)	84	85						86				
Sound pressure level	Cooling	Nom.	dB(A)	2.60						2.60					
Operation range	Air side	Cooling	Min.-Max.	°CDB	-18~-48										
	Water side	Cooling	Min.-Max.	°CDB	-15~-15										
Refrigerant	Type / GWP	R-134a / 1,430													
	Circuits	Quantity	2												
Refrigerant charge	Per circuit	kg		21.0	24.0	26.0	32.0	33.0	34.0		35.0	38.0	40.0		
		TCO <sub>2</sub> Eq		30.0	34.3	37.2	45.8	47.2	48.6		50.1	54.3	57.2		
Piping connections	Evaporator water inlet/outlet (OD)			4"						5"					
Unit	Starting current	Max		A	218	232		276	284		296	406	457	475	
	Running current	Cooling	Nom.	A	135	143	157	173	188	204	220	231	272	280	298
		Max		A	164	183	199	210	221	235	250	291	316	338	360
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400										

(1) Cooling: entering evaporator water temp. 12°C; leaving evaporator water temp. 7°C; ambient air temp. 35°C; full load operation. | Equipment contains fluorinated greenhouse gases. Actual refrigerant charge depends on the final unit construction, details can be found on the unit labels.

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · [www.daikin.eu](http://www.daikin.eu) · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-427\_4 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.